

View Online at <https://aerobasegroup.com/nsn/5935-01-005-3579>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/clamp

**Overall Diameter:**

1.656 inches

**Environmental Protection:**

Heat resistant and shock resistant

**Cable Entrance Diameter:**

Between 0.325 inches and 0.615 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"3, 5-15" single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

15.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Cable Strain Relief Method:**

Cable clamp

**End Application:**

Missile minuteman Igm-30

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping or copper alloy single mating end single contact grouping

**Terminal Type:**

Screw single mating end single contact grouping

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Special Features:**

Hospital grade plug

**Test Data Document:**

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-c-596/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0