NSN 5935-01-005-5023

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-005-5023 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/jackscrew **Overall Length:** Between 1.665 inches and 1.685 inches **Overall Height:** 1.860 inches **Overall Width:** Between 0.820 inches and 0.840 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.134 inches and 0.164 inches **Distance Between Mounting Facility Centers:** Between 1.295 inches and 1.305 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.340 inches **Thread Size:** 0.138 inches **Terminal Location:**

Back single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-01-005-5023

Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium Shell Surface Treatment Specification:	
Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium	
Aluminum alloy Shell Surface Treatment: Cadmium	
Shell Surface Treatment: Cadmium	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, class 1 federal specification single treatment response	
Included Contact Quantity:	
20 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Test Data Document:	
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in s	pecification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on or	certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unc	
Specification Data:	
81349-mil-c-28748/9 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	