## NSN 5935-01-005-5159

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-005-5159

| Body Style:   |
|---|
| Straight shape, external coupling   |
| Overall Length:   |
| 0.765 inches  |
| Overall Height:   |
| 1.188 inches  |
| Overall Width:  |
| 1.188 inches  |
| Environmental Protection:   |
| Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant |
| Unthreaded Mounting Hole Diameter:  |
| 0.120 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height:                                       |
| 0.906 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                                     |
| 0.906 inches  |
| Distance From Mounting Shoulder To Front Face:  |
| 0.453 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 19-4 single mating end  |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 7.5 single mating end single contact grouping   |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Detent  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Insert Material:  |

Glass single mating end

## NSN 5935-01-005-5159

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.004 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.