Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-005-5771

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.750 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
20-16 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 Shall Type:
Shell Type:
Solid
Connector Locking Method:
Detent



Thread Length:

0.625 inches

Thread Size:

1.250 inches

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Included Contact Quantity:

7 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

--

Fiig:

A039b0