

View Online at <https://aerobasegroup.com/nsn/5935-01-005-9266>

**Body Style:**

Straight shape w/clamp

**Cable Entrance Diameter:**

Between 0.295 inches and 0.585 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

15.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Shell Type:**

Armored

**Connector Cable Strain Relief Method:**

Cord grip

**End Application:**

Helicopter iroquoisuh-1

**Shell Material:**

Metal ferrous

**Included Contact Quantity:**

2 single mating end single contact grouping

**Test Data Document:**

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0