

View Online at <https://aerobasegroup.com/nsn/5935-01-006-1439>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Diameter:

0.800 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Missile, minuteman Igm-30

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-764, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.