NSN 5935-01-006-2446

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-006-2446

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

1.938 inches

Overall Diameter:

1.625 inches

Environmental Protection:

Moisture resistant

Cable Entrance Diameter:

Between 0.725 inches and 0.760 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

550.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-006-2446 Electrical Plug Connector - Page 2 of 2



| Terminal Type: | |
|-------------------|--|
| Crimp single ma | ating end single contact grouping |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface T | Treatment: |
| Cadmium and n | ickel |
| Shell Surface 1 | Freatment Specification: |
| Qq-p-416 federa | al specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response |
| Included Conta | act Quantity: |
| 100 single matir | ng end single contact grouping |
| Included Conta | act Type: |
| Round pin single | e mating end single contact grouping |
| Precious Mater | rial And Location: |
| Contact surface | is gold |
| Precious Mater | rial And Weight: |
| 0.100 gold grair | ns, troy |
| Precious Mater | rial: |
| Gold | |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | re: |
| | |
| Demilitarizatio | n: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military | y Standard): |
| Mil-g-45204 spe | 90. |