Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-006-5483

Inread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Thread Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end single contact grouping Polarization Method: Renovable single mating end single contact grouping Polarization Method: Sold Connect Locking Method: Bayonet latch Thread Size: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	Thread Class:
Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threade Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Motisture resistant in Degi 40519 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Degi 0.0 Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Length: 0.562 inches Contact Materia! Coper alloy single ma	
Right-hand Body Style: Straight shape, internal coupling Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Matting End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Mottage mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size 0.562 inches Thread Length: 0.562 inches Thread Length: 0.562 inches Thread Length: 0.562 inches Contact Size Ostage mating end single contact grouping Contact Materia!	
Body Style: Straight shape, internal coupling Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Back shell Outcact Renovability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Back shell Outcact Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Ereminal Location: Back single mating end single contact grouping Contact Material: Corpor alloy single mating end single contact grouping	
Straight shape, internal coupling Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Taremial Location: Back single mating end single contact grouping Chreat Size: 0.562 inches Teremial Location: Back single mating end single contact grouping Contact Material: Cooper alloy single mating end single contact grouping	-
Overall Length: 0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Date tatch Thread Length: 0.219 inches Thread Size: 0.562 inches Taremial Location: Back single mating end single contact grouping	
0.766 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.4219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping	
Overall Diameter: 0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Contact Locking Method: Bayonet latch Thread Length: 0.562 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	-
0.859 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantiy: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Erminal Location: Back single mating end single contact grouping Contact Mether] Back single mating end single contact grouping Contact Mether] Back single mating end single contact grouping Contact Mether] Bayonet latch Contact Size: 0.562 inches Contact Size: 0.562	
Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantiy: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Regway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.562 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping	
Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Polarization Arrangement Style: Removable single mating end Polarization Method: Reyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
Mating End Quantity: 1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
1 Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Contact Position Arrangement Style: 40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
40519 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
Removable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Bayonet latchThread Length:0.219 inchesThread Size:0.562 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:	
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Bayonet latchThread Length:0.219 inchesThread Size:0.562 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:	
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping	
0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Shell Type:SolidConnector Locking Method:Bayonet latchThread Length:0.219 inchesThread Size:0.562 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:	
Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	Shell Type:
Bayonet latch Thread Length: 0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Thread Length:0.219 inchesThread Size:0.562 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:	
0.219 inches Thread Size: 0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	
Thread Size:0.562 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:	Thread Length:
0.562 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	0.219 inches
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	Thread Size:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	0.562 inches
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:	Terminal Location:
Copper alloy single mating end single contact grouping Contact Surface Treatment:	Back single mating end single contact grouping
Contact Surface Treatment:	Contact Material:
	Copper alloy single mating end single contact grouping
Gold single mating end single contact grouping and silver single mating end single contact grouping	Contact Surface Treatment:
	Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:	Terminal Type:
Crimp single mating end single contact grouping	Crimp single mating end single contact grouping
Shall Material	Shell Material:
Sheh material:	Aluminum alloy
Sheh Material:	Aluminum alloy

NSN 5935-01-006-5483

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Contact designation 10-99

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.007 gold grains, troy and 0.007 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.