## NSN 5935-01-006-6207

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-006-6207

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.926 inches
Overall Diameter:
1.108 inches
Cable Entrance Diameter:
0.547 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-22 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
550.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet slot
Bayonet slot  Connector Cable Strain Relief Method:
·
Connector Cable Strain Relief Method:
Connector Cable Strain Relief Method: Cable clamp
Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material:
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment:
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material:
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Rubber single mating end
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Rubber single mating end Terminal Type:
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Rubber single mating end Terminal Type: Solder well single mating end all contact groupings

Anodize

## NSN 5935-01-006-6207

Electrical Plug Connector - Page 2 of 2



Included Contact Quan	tity:
-----------------------	-------

4 single mating end 2nd contact grouping

**Included Contact Type:** 

Round socket single mating end all contact groupings

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.004 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0