

View Online at <https://aerobasegroup.com/nsn/5935-01-006-8208>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape quick connect

**Overall Length:**

1.342 inches

**Overall Width:**

0.688 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Mounting Facility Thickness:**

0.406 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Bnc all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

1000.0 megahertz all mating ends single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

90.0 and 180.0 and 270.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thread Size:**

0.438 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0