Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-1661

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.298 inches and 1.318 inches
Overall Height:
Between 1.117 inches and 1.133 inches
Overall Width:
Between 1.117 inches and 1.133 inches
Environmental Protection:
Moisture proof and pressure proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.901 inches and 0.911 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.901 inches and 0.911 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-37 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.875 inches

Mil-std (military Standard):

Mil-g-45204 spec.



Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Contact Surface Treatment Specification:	
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatment:	
Chromium	
Shell Material Specification:	
Qq-a367, comp 6061, t6 federal specification single material response	
Included Contact Quantity:	
37 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.037 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	1
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Un	
Specification Data:	
81349-mil-c-81511/41 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Filg:	
A039b0	