NSN 5935-01-007-1663

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-1663

view Offline at https://acrobasegroup.com/hsh/0300-01-1000
Body Style:
Straight shape
Overall Length:
Between 2.714 inches and 2.744 inches
Overall Height:
0.830 inches
Overall Width:
Between 0.609 inches and 0.694 inches
Environmental Protection:
Moisture proof and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
Between 2.495 inches and 2.505 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Qq-p-416, type 2, class 2 federal specification single treatment response

NSN 5935-01-007-1663

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
For use w/0.094 in. Thk board w/0.040 in. Diameter pins
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/24 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0