Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-007-2581



Thread Class: 2b Thread Direction:
Inread Direction:
Diskt hand
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.980 inches
Overall Diameter:
Between 0.548 inches and 0.578 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Frequency Rating:
11000.0 megahertz single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:

Plastic polytetrafluoroethylene single mating end

NSN 5935-01-007-2581 Electrical Plug Connector - Page 2 of 2



	nal Type:
-	single mating end single contact grouping
	et Material Specification:
	 comp ht federal specification single material response single mating end single contact grouping
Copper	anoy Surface Treatment:
Silver	surface Treatment:
	Surface Treatment Specification:
	-
	65, type 2, grade a federal specification single treatment response
	Iaterial Specification: 26, comp 22, 1/2 h federal specification single material response
	Material Specification: 9468 military specification single material response single mating end
-	ed Contact Quantity:
	e mating end single contact grouping
-	ed Contact Type:
	l pin single mating end single contact grouping
	I Features:
-	t designation thc
	us Material And Location:
	t surface gold
	us Material And Weight:
	pold grains, troy
-	us Material:
Gold	
	I Series Designator:
Unef	5
Shelf L	.ife:
N/a	
Unit Of	f Measure:
Demili	tarization:
No	
Fiig:	
A039b0	D
Mil-std	(military Standard):
Mil-n-1	9468 spec.