Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-2650

Tread Oracs:         Zb         Tread Oracs:         Tread Oracs:         Tread Oracs:         Sei Matrial:	
Thread Direction:         Right-hand         Sel Matrial:         Rubber, silicone base         Overall Length:         Between 1.110 inches and 1.140 inches         Overall Height:         Between 1.042 inches and 1.072 inches         Overall Meight:         Between 1.281 inches and 1.072 inches         Overall Widh:         Between 1.281 inches and 1.072 inches         Cable Opening Diameter:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         Sea Type:         Performed packing         Size Designation:         14         Mouting Facility Type And Quantity:         1 threaded coupling         Thready Gly Per Inch (tpl):         20         Thread Size:         0.875 inches         Matrial:         Aurinum alloy         Surface Treatment:         Nickal         Stright type web cable clamp         Stright type web cable clamp </th <th>Thread Class:</th>	Thread Class:
Right-hand   Seal Material:   Rubber, sillcone base   Overall Length:   Edween 1.101 inches and 1.140 inches   Overall Height:   Between 1.042 inches and 1.072 inches   Overall Width:   Between 1.042 inches and 1.034 inches   Cable Opening Diameter:   Between 0.500 inches and 0.750 inches   Cable Opening Quantity:   Preformed packing   Seal Type:   Preformed packing   Star Designation:   1   1   Star Designation:   20   Star Designation:   21   Star Designation:   22   Star Designation:   23   Star Designation:   24   Star Designation:   25   Star Designation:   26   Star Designation:   27   Star Designation:   28    Star Designation: </th <th></th>	
Seal Material:         Rubber, silicone base         Overall Langth:         Between 1.110 inches and 1.140 inches         Overall Heigh:         Between 1.042 inches and 1.072 inches         Overall Width:         Between 1.042 inches and 1.041 inches         Overall Width:         Between 0.500 inches and 1.341 inches         Cable Opening Quantity:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         Proformed packing         Proformed packing         Partormed packing         Partormed packing         1         1         1         1         1         1         1         Proformed packing         20         Proformed packing         11         11         11         12         20         13         14         14         20         20         20         20         20         20         20         20         20         20	
Rubber, silicone base         Overall Length:         Between 1.10 inches and 1.10 inches         Overall Height:         Between 1.20 inches and 1.072 inches         Overall Wildth:         Between 1.281 inches and 1.341 inches         Cable Opening Diamete:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         Sea Type:         Preformed packing         Size Designation:         14         Mounting Facility Type And Quantity:         1 threaded coupling         Thread Size:         0.375 inches         Maerial:         Autimum alloy         Surface Teatment:         Nickel         Straght type wickable clamp         Surface Treatment:         Nickel         Straght type wickable clamp         Surface Treatment:         Nickel         Straght type wickable clamp         Surface Treatment:         Nickel         Straght type wickable clamp         Butter Teater Straget S	
Serveral Length:         Between 1.110 inches and 1.140 inches         Overall Widh:         Between 1.281 inches and 1.072 inches         Overall Widh:         Between 1.281 inches and 1.341 inches         Cable Opening Diameter:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         Sear Type:         Preformed packing         Size Disgnation:         14         Monting Facility Type And Quantity:         14         Monting Facility Type And Quantity:         14         Monting Facility Type And Quantity:         15         16         17         Strate Size:         0.875 inches         Material:         0.875 inches         Material:         0.875 inches         Strate Teatment:         Nickel         Straight type website clamp         Straight type website clamp         Interact Teatment:         Nickel         Straight type website clamp         Interact Teatment:         Nickel         Straight type website clamp         Interact Teatment:	
Between 1.110 inches and 1.140 inches Overall Heigh: Between 1.022 inches and 1.072 inches Overall Widt: Between 1.281 inches and 1.341 inches Cable Opening Diamete: Between 0.500 inches and 0.750 inches Cable Opening Quantity: 1 Between 0.500 inches and 0.750 inches Cable Opening Quantity: 1 Preformed packing Freformed packing Size Designation: 14 Mounting Facility Type And Quantity: 1 Intread Quy Per Inch (tpi): 20 Freformed packing Size Designation: 14 Mounting Racility Dese Methy Size	
Overall Height:         Between 1.042 inches and 1.072 inches         Overall Width:         Between 1.281 inches and 1.341 inches         Cable Opening Diameter:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         State Trape:         Preformed packing         Size Designation:         14         Monting Facility Type And Quantity:         1         14         Monting Facility Type And Quantity:         1         14         Monting Facility Type And Quantity:         1         14         Monting Facility Type And Quantity:         10         14         Monting Facility Type And Quantity:         10         14         Monting Facility Type And Quantity:         10         Threaded coupling         Threaded coupling         Cate Coupling Categories         10         State Gister         10         State Gister         11         11         12         12         State Giste Catemp         Stat	
Between 1.042 inches and 1.072 inches  Overall Width: Between 1.281 inches and 1.341 inches  Cable Opening Diameter: Between 0.500 inches and 0.750 inches  Cable Opening Diameter: Between 0.500 inches and 0.750 inches  Cable Opening Diameter: I  Cable Opening Diam	
Nevral Width:         Between 1.281 inches and 1.341 inches         Cable Opening Diameter:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         Cable Opening Quantity:         1         Seal Type:         Preformed packing         Size Designation:         14         Mounting Facility Type And Quantity:         1 threadd coupling         Threadd coupling         Threadd Size:         0.875 inches         Material:         Auminum alloy         Stright Type w/cable clamp         Stright type w/cable clamp         Stright type w/cable clamp         Infreed Series Designator:         Nickel         Thread Series Designator:         Nickel         Sher Threit         Nickel      <	
Beween 1.281 inches and 1.341 inches Cable Opening Diameter: Between 0.500 inches and 0.750 inches Cable Opening Quantity: 1 1 Seal Type: Preformed packing Size Designation: 14 Mounting Facility Type And Quantity: 1 threadd coupling Threadd coupling Threadd Size: 0.875 inches Material: Auminum alloy Surface Treatment: Nickel Style Designator: Stright Type wicable clamp Stright Type wicable clamp Lamp Lamp Lamp Lamp Lamp Lamp Lamp L	
Cable Opening Quantity:         Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         Seal Type:         Proformed packing         Size Designation:         Size Designation:         14         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Quy Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Stringint type w/cable clamp         Stringint type w/cable clamp         Stringint type w/cable scienco         Nickel         Thread Series Designator:         Nickel         Stringint type w/cable scienco         Nickel         Theread Series Designator:         Nickel         String Series Designator:         String Series Designator: <th></th>	
Between 0.500 inches and 0.750 inches         Cable Opening Quantity:         1         Seal Type:         Preformed packing         Size Designation:         14         Mouning Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Stright type w/cable clamp         Stright type w/cable clamp         Interded Series Designator:         Indeg         Nickel         Thread Series Designator:         Nickel         Stright type w/cable clamp         Stright type w/cable clamp         Interd Series Designator:         Indeg         Stright type w/cable clamp         Stright type w/cable clamp         Interd Series Designator:         Nickel         Thread Series Designator:         Interd Series Designator:         Nickel         Stright type w/cable clamp         Interd Series Designator:         Nickel         Stright type w/cable clam	
Cable Opening Quantity:         1         Seal Type:         Preformed packing         Size Designation:         14         Mounting Facility Type And Quantity:         1 threaded coupling         Threaded coupling         Threaded Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Straight type w/cable clamp         Surface Treatment:         Nickel         Thread Series Designator:         Inford Measure:         Nickel         Thread Series Designator:         Nickel         Thread Series Designator:         Nickel         Thread Series Designator:         Nickel         Straight type w/cable clamp         Straight type w/cable clamp         Straight type w/cable clamp         Thread Seri	
1         Seal Type:         Preformed packing         Size Designation:         14         Mounting Facility Type And Quantity:         14         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Style Designator:         Stratight type w/cable clamp         Surface Treatment:         Nickel         Fored Series Designator:         Unef         Stratight type w/cable clamp         Surface Treatment:         Nickel         Thread Series Designator:         Unef         Sheff Life:         Nickel         Chef Life:         Nickel         Dit Of Measure:         Tot Company:         The Company:         Nickel         Stratignation:         Dit Of Measure:         Tot Company:         Tot Company:         Strate Comp         Strate Comp	
Seal Type:         Preformed packing         Size Designation:         14         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Straight type w/cable clamp         Surface Treatment:         Nickel         Straight type model clamp         Surface Treatment:         Nickel         Surface Treatment:         Nickel         Surface Treatment:         Nickel         Cherd Series Designator:         Unef         Surface Treatment:         Nickel         Cherd Series Designator:         Unef         Surface Treatment:         Nickel         Cherd Series Designator:         Unef         Surface Treatment:         Nickel         Surface Treatment:         Nickel         Surface Treatment:         Dief Life:         Life Measure:         Life Measu	Cable Opening Quantity:
Preformed packing Size Designation: 14 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thready Cay Per Inch (tpi): 20 Thread Size: 20 Thread Size: 20 Strates Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Stratight type w/cable clamp Stratight type w/cable clamp Strates Nickel Nickel Strates Nickel Strates S	
Size Designation:   14   Mounting Facility Type And Quantity:   1 threaded coupling   Thready Qty Per Inch (tpi):   20   Thread Size:   0.875 inches   Material:   Aluminum alloy   Surface Treatment:   Nickel   Striaght type w/cable clamp   Surface Treatment:   Nickel   Striaght type w/cable clamp   Surface Treatment:   Nickel   Striaght type w/cable clamp   Diread Series Designator:   Unef   Sheff Life:   Nickel   Striaght type w/cable clamp   Diread Series Designator:   Unef   Diread Series Designator:   Unef   Sheff Life:   Nickel   Thread Series Designator:   Unef   Sheff Life:   Nickel   Thread Series Designator:   Unef   Sheff Life:   Nickel   Thread Series Designator:   Unef   Sheff Life:   Nickel   Striaght type w/cable clamp	Seal Type:
14         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Stright type w/cable clamp         Stright type w/cable clamp         Nickel         Thread Series Designator:         Unef         Shift Life:         Nickel         Duef         Duef      Duef         Due	Preformed packing
Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Stright type w/cable clamp         Stright type w/cable clamp         Nickel         Durface Treatment:         Nickel         Stright type w/cable clamp         Stright type w/cable clamp         Mickel         Thread Series Designator:         Unef         Sheff Life:         N/a         Unit of Measure:         Lift of Measure:         maint         Theol Series Designator:	Size Designation:
<pre>1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.875 inches 0.875 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Incread Series Designator: Unef Shelf Life: N/a Linef Shelf Life: N/a Linef Function: Component Component</pre>	14
Thready Qty Per Inch (tpi):         20         Thread Size:         0.875 inches         0.875 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Straight type w/cable clamp         Surface Treatment:         Nickel         Duef         Shelf Life:         N/a         Unef         Shelf Life:         N/a         Unef Complement:         Suffice Complement:         N/a         Differ:         N/a         Differ:         N/a         Differ:         N/a         Differ:         Prot         Differ:         N/a         Differ:         Differ:         Differ:         Differ:         Differ:         Differ:         Differ:	Mounting Facility Type And Quantity:
20 Thread Size: 0.875 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clam	1 threaded coupling
Thread Size:0.875 inchesMaterial:Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUni of Measure:Emilitarization:	Thready Qty Per Inch (tpi):
0.875 inches Material: Material: Aluminum alloy Aufrace Treatment: Nickel Style Designator: Straight type w/cable clamp Staright type w/cable clamp Nickel Nickel Unef Stelf Life: N/a Linef Stelf Life: N/a Ditl of Measure:	20
Material:Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aDit Of Measure:Demilitarization:	Thread Size:
Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Lithe: N/a Ditt Of Measure:	0.875 inches
Surface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:	Material:
Nickel Style Designator: Straight type w/cable clamp Surface Treatment: Nickel Nickel Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Function: Component of the straight of the straightoo straight of the straightoo strai	Aluminum alloy
Style Designator:         Straight type w/cable clamp         Surface Treatment:         Nickel         Thread Series Designator:         Unef         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:	Surface Treatment:
Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	Nickel
Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: 	Style Designator:
Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	Straight type w/cable clamp
Thread Series Designator:   Unef   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	
N/a Unit Of Measure:  Demilitarization:	
Unit Of Measure:  Demilitarization:	Shelf Life:
 Demilitarization:	
	Unit Of Measure:
No	Demilitarization:
	No

## NSN 5935-01-007-2650

Electrical Connector Backshell - Page 2 of 2

**Fiig:** A10100

