NSN 5935-01-007-5701

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-5701 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.406 inches and 1.471 inches **Overall Height:** Between 1.242 inches and 1.258 inches **Overall Width:** Between 1.242 inches and 1.258 inches **Environmental Protection:** Moisture proof and pressure proof and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.964 inches and 0.974 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.964 inches and 0.974 inches **Distance From Mounting Shoulder To Front Face:** Between 0.894 inches and 0.906 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 84.0 and 152.0 and 204.0 and 334.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.000 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-007-5701

Electrical Receptacle Connector - Page 2 of 2



Contact	Material:
---------	-----------

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-367, comp 6061, t6 federal specification single material response

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Nο Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.