

View Online at <https://aerobasegroup.com/nsn/5935-01-007-6391>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

0.960 inches

Overall Diameter:

0.400 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.085 inches

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Contact designation sma

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-c-39012/79 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.