## NSN 5935-01-007-6402

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-6402

| Thread Class:   |
|---|
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, internal coupling   |
| Overall Length:   |
| 0.687 inches  |
| Overall Diameter:   |
| 0.250 inches  |
| Cable Entrance Diameter:  |
| 0.118 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| Sm single mating end  |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Internally threaded coupling ring   |
| Connector Cable Strain Relief Method:   |
| Compression nut   |
| Thread Size:  |
| 0.190 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Insert Material:  |
| Plastic polytetrafluoroethylene single mating end   |
| Contact Surface Treatment Specification:  |
| Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Contact Material Specification:   |

Contact Material Opecinication

Qq-530, 1/2 h federal specification single material response single mating end single contact grouping

## **NSN 5935-01-007-6402**Electrical Plug Connector - Page 2 of 2



| Shell Material:   |
|---|
| Copper alloy  |
| Shell Surface Treatment:  |
| Gold  |
| Shell Surface Treatment Specification:  |
| Mil-g-45204, type 1, class 2 military specification single treatment response |
| Shell Material Specification:   |
| Qq-b-626 federal specification single material response                       |
| Insert Material Specification:  |
| Mil-p-19468 military specification single material response single mating end |
| Included Contact Quantity:  |
| 1 single mating end single contact grouping                                   |
| Included Contact Type:  |
| Coaxial socket single mating end single contact grouping                      |
| Special Features:   |
| Contact designation sma   |
| Precious Material And Location:   |
| Contact and shell surfaces gold   |
| Precious Material And Weight:   |
| 0.105 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-g-45204 spec.   |
|   |
|   |