## NSN 5935-01-007-6412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-007-6412 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.344 inches **Overall Diameter:** 0.906 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 20 and 20 **Thread Size:** 0.812 inches and 0.812 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Metal **Shell Surface Treatment:** 

Silver

## NSN 5935-01-007-6412

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 4 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surface silver **Precious Material And Weight:** 0.020 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0