NSN 5935-01-008-5088

Electrical Plug Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-008-5088 |
|---|
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.438 inches |
| Overall Diameter: |
| 1.656 inches |
| Environmental Protection: |
| Corrosion resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 20-41 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Rubber silicone class q single mating end |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 41 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Included Contact Type: |

N/a

Shelf Life:

NSN 5935-01-008-5088

Electrical Plug Connector - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A039b0