

View Online at <https://aerobasegroup.com/nsn/5935-01-008-5820>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

0.500 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.102 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Distance From Mounting Shoulder To Front Face:

0.310 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Mil-g-14548, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

Insert Material Specification:

Zz-r-765, class 2b, grade 65-75 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-14548 spec.