Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-008-5820

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 0.500 inches |
| Environmental Protection: |
| Moisture resistant and vibration resistant and salt water resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.102 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.340 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.340 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.310 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 36 |
| Thread Size: |
| 0.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |



| Contact Surface Treatment: |
|---|
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber synthetic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-14548, type 2, class 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530, cond 1/2 hard federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Steel comp 303 |
| Shell Material Specification: |
| Qq-s-764, type 303, cond a federal specification single material response |
| Insert Material Specification: |
| Zz-r-765, class 2b, grade 65-75 federal specification single material response single mating end |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-14548 spec. |
| |
| |