Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-008-8549

view Online at https://aerobasegroup.com/nsi//0000-00-00-00-00-00-00-00-00-00-00-00-
Body Style:
Straight shape
Overall Length:
2.060 inches
Overall Width:
0.290 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
1.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Contact
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Wire wrap single mating end single contact grouping
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:

0.026 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0

