

View Online at <https://aerobasegroup.com/nsn/5935-01-009-0198>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 0.945 inches and 0.955 inches

**Overall Diameter:**

Between 0.415 inches and 0.425 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Cable Entrance Diameter:**

Between 0.075 inches and 0.081 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

110.0 and 250.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Crimp type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and nickel

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

1.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0