Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-009-2963

Piread Class: 2b Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 2.378 inches Overall Diameter: 2.188 inches Threaded Device Type: Coupling facility Maing End Quantity: Coupling facility Maing End Quantity: Renovable single mating end single contact grouping Polarization Method: Renovable single mating end single contact grouping Polarization Method: Row Sold Concort Cocking Method: Renovable single mating end single contact grouping Pole Sold Concort Locking Method: Internally threaded coupling ring Thread Size: 1.750 inches Cold Concort Locking Meting end single contact grouping Contart Material: Cold single mating end single contact grouping Contart Surface Treatment: Sold single mating end single contact grouping Contart Surface Treatment:	
Thread Direction: Right-hand Body Style: Straigt shape, internal coupling Overall Length: 2.375 inches Overall Dimeter: 2.188 inches Threaded Device Type: Coupling facility Mating End Quantity: Threaded Device Type: Coupling facility Mating End Quantity: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Inser Position In Deg: Ool Shell Type: Solid Chreace Size: 1.750 inches Threaded Size: 1.750 inches Cotart Material: Gotpare alloy single mating end single contact grouping Contact Material: Giver single mating end single contact grouping Cotact Material: Rubber single mating end single contact grouping Cotact Material: Rubber single mating end single contact grouping Cotact Material: Rubber single mating end single contact grouping Cotact Internet:	Thread Class:
Right-hand Body Style: Straight shape, internal coupling Overall Length: 2.375 inches Overall Diameter: 2.188 inches Threade Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removabile single mating end single contact grouping Polarization Method: Insert Position In Deg: 0.0 Shell Type: Solid Concert Locking Method: Internally threaded coupling ring Threaded Diver Ipp: Solid Concert Locking meting end single contact grouping Pherization Method: Solid Concert Locking Method: Internally threaded coupling ring Threaded Size: 1.750 inches Terneid Location: Back single mating end single contact grouping Contact Material: Goper alley single mating end single contact grouping Contact Stafe Internally the adding end single contact grouping Contact Stafe Contact Stafe Material: Ruber single mating end single contact grouping Contact Stafe Contact Stafe <	2b
Body Style: Straight shape, internal coupling Overall Length: 2:375 inches Overall Diameter: 2:188 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Solid Concort Locking Method: Internally threaded coupling ring Threaded Device Type: Solid Concort Locking Method: Internally threaded coupling ring Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Ruber single mating end single contact grouping Fiber single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Fiber single mating end single contact	Thread Direction:
Straight shape, internal coupling Overall Length: 2.375 inches Overall Diameter: 2.188 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 1.750 inches Coper alloy single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end si	Right-hand
Overall Length: 2.375 inches Overall Diameter: 2.188 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Copper alloy single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Cipper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Material: Ruber	Body Style:
2.375 inches Overall Diameter: 2.188 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Rey, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Interaded coupling ring Thread Quaper Inch (tpi): 18 Thread Stae: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Couple mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end single contact grouping Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping S	Straight shape, internal coupling
Overall Diameter:2.188 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Removability:Removable single mating end single contact groupingPolarization Method:Key, multiple key grooveInsert Position In Deg:0.0SolidConnector Locking Method:Intready Qty Per Inch (tpi):18Thready Qty Per Inch (tpi):18Thread Size:1.750 inchesContact Surface Treatment:Solige mating end single contact groupingContact Surface Treatment:Sily single mating end single contact groupingContact Surface Treatment:Contact Surface Treatment:Sily single mating end single contact groupingContact Surface Treatment:Sily Surface Treatment:Surface Treatme	Overall Length:
2.188 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Contect Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contect Material: Rooper alloy single mating end single contact grouping Contect Material: Biver single mating end single contact grouping Insert Material: Rubber single mating end single contact grouping Cimental Location: Biver single mating end single contact grouping Contect Surface Treatment: Silver single mating end single contact grouping Cimental Locatio: Rubber single mating end single contact grouping Disert Materia! Rubbe	2.375 inches
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Concectr Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Rober single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Ruber single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Coring single mating end single contact grouping Charter Single mating end single contact grouping Shell Material: Aturnium alloy	Overall Diameter:
Coupling facility Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpl): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Internall Jonation: Silver single mating end single contact grouping Contact Material: Rubber single mating end single contact grouping Internal Type: Crimp single mating end single contact grouping Silver single mating end single contact grouping Cheret Material: Rubber single mating end single contact grouping Silver single mating end single contact grouping Crimp single mating end single contact grouping Shell Material: Alu	2.188 inches
Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Furent Material: Rubber single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end single contact grouping Crimes nating end single contact grouping Cimps single mating end single contact grouping Comper single mating end single contact grouping Cimps ingle mating end single contact grouping Shell Material: Rubber single mating end single contact grouping Shell Material:	Threaded Device Type:
1 Contact Removability: Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Cioper alloy single mating end single contact grouping Furent Material: Rubber single mating end single contact grouping Furent Material: Grimp single mating end single contact grouping Furent Material: Rubber single mating end single contact grouping Crimp single mating end Grimp single mating end single contact grouping Crimp single mating end single contact grouping Shell Material: Autwinum alloy Shell Surface Treatment:	Coupling facility
Contact Removability:Removable single mating end single contact groupingPolarization Method:Key, multiple key grooveInsert Position In Deg:0.0Shell Type:SolidConcector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesEdminal Location:Back single mating end single contact groupingContact Material:Contact Surface Treatment:Silver single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingFirminal Location:Contact Surface Treatment:Silver single mating end single contact groupingContact Surface Treatment:Silver single mating end single contact groupingCrimp single mating end single contact groupingCharter Material:Rubber single mating end single contact groupingCharter Material:Rubber single mating end single contact groupingCharter Material:Corting I Type:Crimp single mating end single contact groupingShell Material:Auminum alloyShell Surface Treatment:	Mating End Quantity:
Removable single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Rubber single mating end single contact grouping Crimp single mating end Type: Crimp single mating end single contact grouping Crimp single mating end Type: Crimp single mating end Silver single mating end Silver single mating end single contact grouping Chart Material: Rubber single mating end single contact grouping Crimp single mating end single contact grouping Shell Material: Aluminu	1
Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber single mating end single contact grouping Cortact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end single contact grouping Cirting single mating end Silver single mating end Silver single mating end Rubber single mating end Terminal Type: Cirting single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	Contact Removability:
Key, multiple key grooveInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Silver single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingInsert Material:Aluminum alloyShell Material:Shell Surface Treatment:Shell Surface Treatment:	Removable single mating end single contact grouping
Insert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingDerminal Type:Crimp single mating end single contact groupingBaterial:Auminum alloyShell Material:Aluminum alloyShell Surface Treatment:	Polarization Method:
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Cisper Ma	Key, multiple key groove
Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerninal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingBrent Material:Silver single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingForminal Type:Crininal Type:Crininal Type:Chart Material:Shell Material:Auminum alloyShell Surface Treatment:Shell Surface Treatment:	Insert Position In Deg:
SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingBorter Surface Treatment:Silver single mating end single contact groupingParent Material:Rubber single mating end single contact groupingForminal Type:Crinp single mating end single contact groupingShell Material:Auminum alloyShell Surface Treatment:	0.0
Connector Locking Method:Internally threaded coupling ringInternally threaded coupling ringThready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingBilver single mating end single contact groupingInsert Material:Rubber single mating end single contact groupingForminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:	Shell Type:
Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Cimp single mating end single contact grouping Shell Material: Aluminum alloy	Solid
Thready Qty Per Inch (tpi):18Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Silver single mating endRubber single mating endCreminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:	Connector Locking Method:
18 Thread Size: 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	Internally threaded coupling ring
Thread Size:1.750 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Silver single mating end single contact groupingInsert Material:Rubber single mating endTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:	Thready Qty Per Inch (tpi):
 1.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: 	18
Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Silver single mating end single contact groupingInsert Material:Rubber single mating endTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:	Thread Size:
Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Silver single mating end single contact groupingInsert Material:Rubber single mating endTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:	
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Silver single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:	
Shell Material: Aluminum alloy Shell Surface Treatment:	
Aluminum alloy Shell Surface Treatment:	
Shell Surface Treatment:	
Chromate	
	Chromate

NSN 5935-01-009-2963

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.030 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0