

View Online at <https://aerobasegroup.com/nsn/5935-01-009-5639>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

2.000 inches

Overall Height:

1.218 inches

Overall Diameter:

0.650 inches

Environmental Protection:

Moisture proof and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.156 inches

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

Mil-prf-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349 - mil-prf-39012/30 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.