NSN 5935-01-009-5659

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-009-5659 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.795 inches and 1.805 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches **Overall Height:** 1.560 inches **Overall Width:** Between 0.695 inches and 0.705 inches **Environmental Protection:** Dripproof and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.400 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:**

Contact Material:

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-009-5659

Electrical Receptacle Connector - Page 2 of 2



Material	

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

54 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.054 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.