

View Online at <https://aerobasegroup.com/nsn/5935-01-009-7587>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

Between 4.270 inches and 4.290 inches

**Overall Height:**

0.692 inches

**Overall Width:**

Between 0.412 inches and 0.432 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.133 inches

**Distance Between Mounting Facility Centers:**

Between 4.026 inches and 4.036 inches

**Board Accommodated Length:**

3.586 inches single board and 3.606 inches single board

**Board Accommodated Width:**

Between 0.071 inches and 0.081 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, @type sdg military specification single material response single mating end

**Included Contact Quantity:**

44 single mating end single contact grouping

**Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.000 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.