Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-009-8512

Body Style: Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response



Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-m-14, type sdg military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.