NSN 5935-01-010-1583

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-010-1583

view Orinine at https://derobasegroup.com/nsi//0900-01-010-1000
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.219 inches
Overall Diameter:
Between 1.469 inches and 1.499 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Cable Entrance Diameter:
0.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
61-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
25.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber silicone class q single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

NSN 5935-01-010-1583

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.012 gold grains, troy and 0.012 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0