Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-010-6165

T L	
	ad Class:
2a	
	ad Direction:
0	t-hand
-	y Style:
	ght shape, external coupling
	rall Length:
	0 inches
Over	rall Height:
1.562	2 inches
Over	rall Width:
Betw	veen 1.557 inches and 1.567 inches
Envi	ronmental Protection:
Hum	idity resistant and pressure proof and shock proof and vibration resistant
Unth	areaded Mounting Hole Diameter:
Betw	een 0.115 inches and 0.125 inches
Cent	ter To Center Distance Between Mounting Facilities Parallel To Height:
1.250	0 inches
Dista	ance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250	0 inches
Dista	ance From Mounting Shoulder To Front Face:
Betw	een 1.245 inches and 1.250 inches
Thre	aded Device Type:
Back	shell
Mati	ng End Quantity:
1	
Cont	tact Position Arrangement Style:
55 ni	umber 20 single mating end
Cont	tact Removability:
Rem	ovable single mating end single contact grouping
Cont	tact Maximum Current Rating In Amps:
7.5 s	ingle mating end single contact grouping
Pola	rization Method:
Key,	multiple key groove
Inse	rt Position In Deg:
336.0	0 and 225.0 and 161.0 and 120.0
Shel	I Туре:
Solid	i de la constante de
Con	nector Locking Method:
Bayo	onet pin
	ad Longth
Thre	ad Length:

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):

18

Thread Size:

1.312 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-83723/72 government specification

Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:



Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.