

View Online at <https://aerobasegroup.com/nsn/5935-01-010-7618>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Wall type

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.276 inches and 3.286 inches

Environmental Protection:

Heat resistant

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.807 inches and 1.817 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 10-30" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Thread Size:

0.138 inches

Terminal Location:

Front single mating end 1st contact grouping

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

L-socket single mating end 1st contact grouping

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81348-w-c-596/33 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0