NSN 5935-01-010-7619

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-010-7619

Body Style:
Straight shape
Overall Length:
4.350 inches
Overall Height:
0.715 inches
Overall Width:
0.250 inches
Distance Between Mounting Facility Centers:
4.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Guide pin/socket Connector Locking Method:
Connector Locking Method:
Connector Locking Method: Post jacksocket
Connector Locking Method: Post jacksocket Terminal Location:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Contact Surface Treatment Specification:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type:
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping
Connector Locking Method: Post jacksocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Insert Material Specification:

Included Contact Quantity:

70 single mating end single contact grouping

NSN 5935-01-010-7619

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.