NSN 5935-01-010-8372

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-010-8372

Thread Class: 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Length:** Between 2.140 inches and 2.160 inches **Overall Height:** 0.712 inches **Overall Width:** Between 0.245 inches and 0.255 inches **Distance Between Mounting Facility Centers:** Between 1.945 inches and 1.955 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.247 inches Thready Qty Per Inch (tpi): 56 and 56 and 56 **Thread Size:** 0.086 inches and 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-m-19833, type gdi-30f military specification single treatment response single mating end single contact grouping **Terminal Type:**

Solder well single mating end single contact grouping

NSN 5935-01-010-8372

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unc and unc

Specification Data:

81349-mil-c-55302/56 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.