## NSN 5935-01-010-8372

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-010-8372

**Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Length:** Between 2.140 inches and 2.160 inches **Overall Height:** 0.712 inches **Overall Width:** Between 0.245 inches and 0.255 inches **Distance Between Mounting Facility Centers:** Between 1.945 inches and 1.955 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.247 inches Thready Qty Per Inch (tpi): 56 and 56 and 56 **Thread Size:** 0.086 inches and 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-m-19833, type gdi-30f military specification single treatment response single mating end single contact grouping **Terminal Type:** 

Solder well single mating end single contact grouping

# NSN 5935-01-010-8372

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

#### **Included Contact Quantity:**

36 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc and unc and unc

#### **Specification Data:**

81349-mil-c-55302/56 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-19833 spec.