NSN 5935-01-010-8373

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-010-8373 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** Between 2.890 inches and 2.910 inches **Overall Height:** Between 0.675 inches and 0.695 inches **Overall Width:** 0.694 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** Between 2.512 inches and 2.532 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1300.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.112 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-01-010-8373

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 40 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Polarized at position a1 **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0