

View Online at <https://aerobasegroup.com/nsn/5935-01-011-1176>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.796 inches

**Overall Diameter:**

Between 1.546 inches and 1.578 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-55 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

142.0

**Shell Type:**

Potting

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

55 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.055 gold grains, troy and 0.055 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0