

View Online at <https://aerobasegroup.com/nsn/5935-01-011-1796>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.342 inches

Overall Width:

0.688 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Mounting Facility Thickness:

0.406 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

1000.0 megahertz all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.438 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0