

View Online at <https://aerobasegroup.com/nsn/5935-01-011-4757>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.656 inches

**Overall Diameter:**

0.312 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Distance From Mounting Shoulder To Front Face:**

0.390 inches

**Mounting Facility Thickness:**

0.156 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

N single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32 and 32

**Thread Size:**

0.250 inches and 0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Special Features:**

Contact designation tsm

**Precious Material And Location:**

Contact surfaces gold and shell surfaces silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.