NSN 5935-01-011-7076

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-011-7076

Body Style:
Straight shape
Overall Length:
0.891 inches
Overall Height:
4.354 inches
Overall Width:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 4.022 inches and 4.030 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.714 inches and 0.722 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
3
Contact Position Arrangement Style:
67 2nd mating end
Contact Removability:
Removable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 2nd mating end 2nd contact grouping
Polarization Method:
2 polarization posts
Shell Type:
Solid
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic epoxy 2nd mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings
Terminal Type:
Crimp all mating ends all contact groupings
Shell Material:
Aluminum alloy a380.0
Shell Surface Treatment:
Cadmium

NSN 5935-01-011-7076

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591, alloy a380 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response 1st mating end

Special Features:

Polarized at position 01, 6 floating eyelets

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.240 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.