Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-011-7672

Body Style: Straight shape **Overall Length:** Between 5.640 inches and 5.660 inches **Overall Height:** 0.565 inches **Overall Width:** Between 0.240 inches and 0.260 inches **Unthreaded Mounting Hole Diameter:** Between 0.110 inches and 0.130 inches **Distance Between Mounting Facility Centers:** Between 5.390 inches and 5.410 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end 1st contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping **Contact Surface Treatment:** Gold single mating end 1st contact grouping **Insert Material:** Plastic polyphenylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end 1st contact grouping **Terminal Type:** Printed circuit single mating end 1st contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end 1st contact grouping **Guide Design And Location:** D shape socket right-hand bottom at 6 oclock **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:**

68 single mating end 1st contact grouping



Included Contact Type: Round pin single mating end 1st contact grouping Precious Material And Location: Contact sufaces gold Precious Material And Weight: 0.090 gold grains, troy

Precious Material:

FIECIOUS Materi

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.