NSN 5935-01-011-9520

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-011-9520

Body Style:

Straight shape

Overall Length:

Between 5.640 inches and 5.660 inches

Overall Height:

0.565 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Unthreaded Mounting Hole Diameter:

Between 0.110 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 5.390 inches and 5.416 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

Terminal Type:

Printed circuit single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping

Guide Design And Location:

D shape socket right-hand bottom at 6 oclock

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

90 single mating end single contact grouping

NSN 5935-01-011-9520

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end 1st contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.090 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.