# NSN 5935-01-012-1274

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-1274

# **Body Style:**

Straight shape, internal coupling

## **Overall Length:**

1.104 inches

# **Overall Diameter:**

1.766 inches

## **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

24-35 single mating end

## Contact Removability:

Removable single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

15.0 and 100.0 and 128.0 and 228.0 and 265.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet latch

## Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

# Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## **Included Contact Quantity:**

128 single mating end single contact grouping

NSN 5935-01-012-1274

Electrical Plug Connector - Page 2 of 2



#### **Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.128 gold grains, troy

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27473 government standard

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.