NSN 5935-01-012-1291

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-1291

| Body Style: |
|---|
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 0.697 inches |
| Overall Height: |
| 1.234 inches |
| Overall Width: |
| 1.234 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.115 inches and 0.130 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.969 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.969 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.442 inches and 0.447 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-6 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |

Aluminum alloy

NSN 5935-01-012-1291

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Cadmium and chromate |
| Included Contact Quantity: |
| 6 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.030 gold grains, troy and 0.030 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Test Data Document: |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-38999 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A020k0 |

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.