# NSN 5935-01-012-1292

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-1292

#### **Body Style:**

Straight shape, external coupling w/backshell

#### **Overall Length:**

0.697 inches

# **Overall Height:**

1.234 inches

# **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

#### Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16-6 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

342.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



# Shell Surface Treatment: Cadmium and chromate Included Contact Quantity: 6 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.006 gold grains, troy and 0.006 silver grains, troy Precious Material:

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-38999 government specification

#### Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

- -----

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-c-38999 spec.