Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-4779

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.578 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

1

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, type sdg-f military specification single

material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.