Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-5580

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 0.590 inches |
| Overall Diameter: |
| 0.406 inches |
| Environmental Protection: |
| Corrosion resistant and salt water resistant |
| Distance From Mounting Shoulder To Front Face: |
| 0.250 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.312 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| |



Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0