Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-6837

#### **Thread Class:**

2a

**Thread Direction:** 

**Right-hand** 

## **Environmental Protection:**

Corrosion resistant and heat resistant and cold resistant and thermal shock resistant and vibration resistant

### Threaded Device Type:

Hub

## Mating End Quantity:

1

# Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic melamine single mating end

### Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-750.Composition a federal specification single material response single mating end single contact grouping

### Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

### **Included Contact Quantity:**

4 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contacts gold

**Precious Material:** 

Gold

### Thread Series Designator:

Unf

#### Shelf Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.