## NSN 5935-01-012-7931

Thread Class: 2a and 2b

Body Style: Straight shape Overall Length:

**Overall Height:** 

**Thread Direction:** 

Right-hand and right-hand

Between 4.340 inches and 4.360 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-012-7931

C	0.540 inches
C	Overall Width:
Е	Between 0.245 inches and 0.255 inches
E	Environmental Protection:
١	Noisture resistant and salt water resistant and vibration resistant
ι	Inthreaded Mounting Hole Diameter:
Е	Between 0.115 inches and 0.125 inches
0	Distance Between Mounting Facility Centers:
4	I.105 inches
1	Threaded Device Type:
C	Coupling facility
Ν	Mating End Quantity:
1	
C	Contact Position Arrangement Style:
2	2 rows of contacts non-inserted board single mating end
C	Contact Removability:
١	Nonremovable single mating end single contact grouping
C	Contact Maximum Current Rating In Amps:
5	5.0 single mating end single contact grouping
F	Polarization Method:
J	lackscrew
C	Connector Locking Method:
J	lackscrew-socket
7	Thread Length:
C	0.130 inches
7	Thread Size:
C	0.086 inches and 0.086 inches
T	Ferminal Location:
S	Side single mating end single contact grouping
C	Contact Surface Treatment:
C	Sold single mating end single contact grouping and nickel single mating end single contact grouping
l	nsert Material:
_	Plastic diallyl phthalate single mating end

## NSN 5935-01-012-7931

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Included Contact Quantity:
70 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.070 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc and unc
Specification Data:
81349-mil-c-55302/61 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiia: