

View Online at <https://aerobasegroup.com/nsn/5935-01-012-8985>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 0.770 inches and 0.790 inches

Overall Height:

Between 0.610 inches and 0.630 inches

Overall Width:

Between 0.200 inches and 0.220 inches

Environmental Protection:

Explosion proof and fungus proof and humidity resistant and shock proof and vibration resistant

Distance Between Mounting Facility Centers:

Between 0.557 inches and 0.567 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.