Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-013-0227

# Body Style:

Rectangular shape, angle

# **Overall Length:**

Between 1.526 inches and 1.556 inches

# **Overall Height:**

Between 0.479 inches and 0.509 inches

### **Overall Width:**

0.731 inches

### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

# Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

# Distance Between Mounting Facility Centers:

Between 1.307 inches and 1.317 inches

# Mating End Quantity:

1 Contact Position Arrangement Style:

15 single mating end

# Contact Removability:

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

#### **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 150.0 degrees celsius

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

### Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Printed circuit single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Shell Material Specification:
Astm-a-620 assn standard single material response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.